

# PAGING ALPHANUMERIC WATCH PAGER

## FEATURES AND BENEFITS

- 420 MHz - 470MHz Frequency
- 1.54"TN colour touch screen
- Covered by reinforced glass with extra strength
- Rugged rubber wristband able to bear a 15kg pulling force
- Receiving Alphanumeric messages with 128 letters at max
- Text display featured by Word wrap
- POCSAG code format
- Selective PC or hand programmable
- Lithium Rechargeable Battery
- Replaceable watch band



TECHNICAL SPECIFICATION	
Output	DC 5V 1A
Frequency	420~470Mhz
Code Format	Poscag
Channel Spacing	20Khz
Frequency Deviation	14.5KHz
Module	FSK
Paging Sensitivity	-110dbm
Bound Rate	512/1200/2400bps
Spurious Emission	<-60dbm
Cap codes Number	8
Display	1.54" TN colour touch screen
Alert by	Flash/Vibrate
Weight	0.14kg

ORDER CODES	
Model:	Description:
HLS-RES-WATCH-ECA	Watch Pager - ECA
HLS-RES-WATCH-FIRE	Watch Pager Fire Marshall

**For more information**  
Contact your Business Manager

**Honeywell**  
140 Waterside Road  
Hamilton Industrial Park  
Leicester, LE5 1TN  
Tel: +44 (0) 203 409 1779

All technical data is correct at the time of publication and is subject to changes without notice. All trademarks acknowledged.  
Installation information: In order to ensure full functionality, refer to the installation instructions as supplied.

Paging watchl V01 | 02/21  
© 2021 Honeywell International Inc.

**Honeywell**